

**In the Claims**

1-19. (cancelled)

20. (currently amended) A method of making a sensor, comprising the steps of:  
providing a substrate;  
providing at least one opening in the substrate;  
placing an electrode proximate to the at least one opening; and  
contacting a dry ionomer membrane to the substrate and electrode ;  
wherein, the ionomer membrane is without equilibration moisture and has been  
without equilibration moisture since inception.

21. (previously presented) The method of claim 20 further comprising the step of  
aligning the at least one opening in the substrate with the electrode for defining a gas  
passage.

22. (cancelled)

23. (previously presented) The method of claim 20 further comprising the step of  
positioning a polymer layer upon the electrode for slowing inputs of gas moving through  
the at least one opening onto a surface of the electrode.

24. (previously presented) The method of claim 20 where the step of providing a  
substrate further includes positioning a counter electrode in contact with the dry iono-  
mer membrane such that upon wetting the dry ionomer membrane the counter elec-  
trode provides an electrical connection.

25. (previously presented) The method of claim 20 where the step of providing a substrate further includes positioning a reference electrode in contact with the dry ionomer membrane such that upon wetting the dry ionomer membrane a reference point is created against which the potential of other electrodes can be measured.

26. (previously presented) The method of claim 20 where the step of providing a dry ionomer membrane further includes obtaining a perfluorosulfonic acid membrane.

27. (previously presented) The method of claim 20 further comprising the step of providing a reservoir in contact with the dry ionomer membrane.

28. (previously presented) The method of claim 27 further comprising the step of filling the reservoir with a liquid.

29. (previously presented) The method of claim 20 further comprising the step of forming at least one hole in the dry ionomer membrane.

30. (previously presented) The method of claim 29 further comprising the step of aligning the at least one hole with the electrode for defining a gas passage.

31. (currently amended) A method of making an electrochemical sensor, comprising the steps of:

- providing a substrate;

- placing an electrode on the substrate;

- contacting a dry ionomer membrane to the substrate and electrode;

- providing a hole in the dry ionomer membrane proximate to the electrode; and

wherein, the ionomer membrane is without equilibration moisture and has been without equilibration moisture since inception.

32. (previously presented) The method of claim 31 further comprising the step of aligning the at least one hole in the dry ionomer membrane with the electrode.